





IMPACT SAFETY GUARDRAILS TRIPLE PLUS





Colour options



IMPACT SAFETY GUARDRAILS TRIPLE PLUS



Colour options



Bollards

Diameter D - mm	Height H - mm	Resistance joules	Anchoring Pullout kN	Total Floor Space mm	IP Grade	Flame Extinguishing Rate
140/120	1230	23 950	580	450	59	UL94: HB

Rails

Number of rails	Diameter D - mm	Height H - mm	Length L - mm	Resistance joules	Total Floor Space mm	IP Grade	Flame Extinguishing Rate
2	55	110	1000-2000-3000	11 900	250	59	UL94: HB
3	55	110	1000-2000-3000	26 500	250	59	UL94: HB

Guards

Diameter D - mm	Height H - mm	Length L - mm	Resistance joules	Anchoring Pullout kN	Total Floor Space mm	IP Grade	Flame Extinguishing Rate
70	130	500-1000-1500-2000	9 369	190	94	59	UL94: HB
100	160	500-1000-1500-2000	19 360	190	140	59	UL94: HB
120	180	500-1000-1500-2000	33 950	190	183	59	UL94: HB

Customized solution and colours upon request



Certifié par TÜV SÜD.
Conforme aux normes BSI - PAS 13 et UNI 11886.

CONTACT FOR CUSTOMER SOLUTIONS: T +39 347 46 74 056 | E info@bambarrier.com | www.bambarrier.com

IMPACT SAFETY GUARDRAILS TRIPLE PLUS



FLEXAFE™

Cutting-Edge Polymer material, designed specifically to absorb high-level impacts in a very small space. It is food-safe, doesn't break or flake, and 100% recyclable.



FOOD SAFE



Resistance to Ultra-Violet
Light DIN-EN-ISO 8777-8
Blue Scale




100% recyclable




Temperature Range -40°
to +50°

ROOTLOCK®


World's most advanced and safe Anchorage System. It helps the floor to absorb violent and repeat vehicles impacts without damaging the floor.




Cutting-edge
Anchorage
System Design



Anti-Shrinkage
Cement



Anchor hole of
the impact
bollards



Anchor hole of
the impact
guards



BAM BARRIER
CRASH TEST LAB